

M型金屬電纜固定頭
M Type Metal Cable Glands




→ M

材料：鍍鍍黃銅
固定連接組件：採用UL認可的尼龍材料
防水圈：丁腈橡膠（可定制耐侯橡膠）
O型圈：耐侯橡膠
工作溫度：-40℃至100℃

Material:
Fixture pack:
Hermetic seal:
O-Ring:
Working temperature: -40℃ to 100℃

Nickel-plated brass
PA (NYLON), UL 94 V-2
NBR, (EPDM Upon Request)
EPDM

■ PROFILE



Thread ØD1	ØD2 mm	H mm	GL mm	ØD mm	Beisit No.	Article No.
M 12 x 1,5	3-6,5	19	6,5	14	M1207BR	1.110.1201.0000
M 12 x 1,5	2-5	19	6,5	14	M1205BR	1.110.1201.2000
M 16 x 1,5	4-8	21	6	17/19	M1608BR	1.110.1601.0000
M 16 x 1,5	2-6	21	6	17/19	M1606BR	1.110.1601.2000
M 16 x 1,5	5-10	22	6	20	M1610BR	1.110.1631.0000
M 20 x 1,5	6-12	23	6	22	M2012BR	1.110.2001.0000
M 20 x 1,5	5-9	23	6	22	M2009BR	1.110.2001.2000
M 20 x 1,5	10-14	24	6	24	M2014BR	1.110.2031.0000
M 25 x 1,5	13-18	25	7	30	M2518BR	1.110.2501.0000
M 25 x 1,5	9-16	25	7	30	M2516BR	1.110.2501.2000
M 32 x 1,5	18-25	31	8	40	M3225BR	1.110.3201.0000
M 32 x 1,5	13-20	31	8	40	M3220BR	1.110.3201.2000
M 40 x 1,5	22-32	37	8	50	M4032BR	1.110.4001.0000
M 40 x 1,5	20-26	37	8	50	M4026BR	1.110.4001.2000
M 50 x 1,5	32-38	37	9	57	M5038BR	1.110.5001.0000
M 50 x 1,5	25-31	37	9	57	M5031BR	1.110.5001.2000
M 63 x 1,5	37-44	38	10	64/68	M6344BR	1.110.6301.0000
M 63 x 1,5	29-35	38	10	64/68	M6335BR	1.110.6301.2000
★: 非常規螺紋 Non-Standard Thread						
★ M 18 x 1,5	5-10	22	6	20	M1810BR	1.110.1801.0000
★ M 18 x 1,5	3-7	22	6	20	M1807BR	1.110.1801.2000
★ M 22 x 1,5	10-14	24	6	24	M2214BR	1.110.2201.0000
★ M 22 x 1,5	7-12	24	6	24	M2212BR	1.110.2201.2000
★ M 27 x 1,5	13-18	25	7	30	M2718BR	1.110.2701.0000
★ M 27 x 1,5	9-16	25	7	30	M2716BR	1.110.2701.2000

專利產品 Patented product.

