

M-加長型金屬電纜固定頭

M-Length Metal Cable Glands




→ M-Length



材料: 鍍銀黃銅
 固定連接組件: 採用UL認可的尼龍材料
 防水圈: 丁腈橡膠, (可定制耐候橡膠)
 O型圈: 耐候橡膠
 工作溫度: -40°C至100°C

Material: Nickel-plated brass
 Fixture pack: PA (NYLON), UL 94 V-2
 Hermetic seal: NBR, (EPDM Upon Request)
 O-Ring: EPDM
 Working temperature: -40°C to 100°C

PROFILE



Thread ØD1	螺絲 mm	H mm	GL mm	螺帽 mm	Beisit No.	Article No.
M 12 x 1,5	3-6,5	19	10	14	M1207BRL	1.110.1201.0100
M 12 x 1,5	2-5	19	10	14	M1205BRL	1.110.1201.2100
M 16 x 1,5	4-8	21	10	17/19	M1608BRL	1.110.1601.0100
M 16 x 1,5	2-6	21	10	17/19	M1606BRL	1.110.1601.2100
M 16 x 1,5	5-10	22	10	20	M1610BRL	1.110.1631.0100
M 20 x 1,5	6-12	23	10	22	M2012BRL	1.110.2001.0100
M 20 x 1,5	5-9	23	10	22	M2009BRL	1.110.2001.2100
M 20 x 1,5	10-14	24	10	24	M2014BRL	1.110.2031.0100
M 25 x 1,5	13-18	25	12	30	M2518BRL	1.110.2501.0100
M 25 x 1,5	9-16	25	12	30	M2516BRL	1.110.2501.2100
M 32 x 1,5	18-25	31	12	40	M3225BRL	1.110.3201.0100
M 32 x 1,5	13-20	31	12	40	M3220BRL	1.110.3201.2100
M 40 x 1,5	22-32	37	15	50	M4032BRL	1.110.4001.0100
M 40 x 1,5	20-26	37	15	50	M4026BRL	1.110.4001.2100
M 50 x 1,5	32-38	37	15	57	M5038BRL	1.110.5001.0100
M 50 x 1,5	25-31	37	15	57	M5031BRL	1.110.5001.2100
M 63 x 1,5	37-44	38	15	64/68	M6344BRL	1.110.6301.0100
M 63 x 1,5	29-35	38	15	64/68	M6335BRL	1.110.6301.2100
★:非常規螺紋 Non-Standard Thread						
★ M 18 x 1,5	5-10	22	10	20	M1810BRL	1.110.1801.0100
★ M 18 x 1,5	3-7	22	10	20	M1807BRL	1.110.1801.2100
★ M 22 x 1,5	10-14	24	10	24	M2214BRL	1.110.2201.0100
★ M 22 x 1,5	7-12	24	10	24	M2212BRL	1.110.2201.2100
★ M 27 x 1,5	13-18	25	12	30	M2718BRL	1.110.2701.0100
★ M 27 x 1,5	9-16	25	12	30	M2716BRL	1.110.2701.2100

專利產品 Patented product.



M
PG
NPT
G(PF)
MG
Multiple-Entry
EMC
Ventilation Plug
Wiring Accessories
Waterproof Enclosure
Flexible Pipe Fitting
Flexible Pipe
Composite Cable Glands