

PG型金屬電纜固定頭

PG Type Metal Cable Glands




→ PG



材料: 鍍鎳黃銅
固定連接組件: 採用UL認可的尼龍材料
防水圈: 丁腈橡膠, (可定制耐侯橡膠)
O型圈: 耐侯橡膠
工作溫度: -40°C至100°C

Material: Nickel-plated brass
Fixture pack: PA (NYLON), UL 94 V-2
Hermetic seal: NBR, (EPDM Upon Request)
O-Ring: EPDM
Working temperature: -40°C to 100°C

PROFILE



Thread ØD1	ØD mm	H mm	GL mm	ØH mm	Beisit No.	Article No.
PG 7	3-6,5	19	5	14	P0707BR	1.110.0701.0200
PG 7	2-5	19	5	14	P0705BR	1.110.0701.2200
PG 9	4-8	21	6	17	P0908BR	1.110.0901.0200
PG 9	2-6	21	6	17	P0906BR	1.110.0901.2200
PG 11	5-10	22	6	20	P1110BR	1.110.1101.0200
PG 11	3-7	22	6	20	P1107BR	1.110.1101.2200
PG 13,5	6-12	23	6,5	22	P13512BR	1.110.1301.0200
PG 13,5	5-9	23	6,5	22	P13509BR	1.110.1301.2200
PG 16	10-14	24	6,5	24	P1614BR	1.110.1601.0200
PG 16	7-12	24	6,5	24	P1612BR	1.110.1601.2200
PG 21	13-18	25	7	30	P2118BR	1.110.2101.0200
PG 21	9-16	25	7	30	P2116BR	1.110.2101.2200
PG 29	18-25	31	8	40	P2925BR	1.110.2901.0200
PG 29	13-20	31	8	40	P2920BR	1.110.2901.2200
PG 36	22-32	37	8	50	P3632BR	1.110.3601.0200
PG 36	20-26	37	8	50	P3626BR	1.110.3601.2200
PG 42	32-38	37	9	57	P4238BR	1.110.4201.0200
PG 42	25-31	37	9	57	P4231BR	1.110.4201.2200
PG 48	37-44	38	10	64	P4844BR	1.110.4801.0200
PG 48	29-35	38	10	64	P4835BR	1.110.4801.2200

專利產品 Patented product.

