

PG型/M/G (PF) 型金属六角螺母 PG Type/M Type/G(PF) Type Metal LockNuts

→ PG/M/G(PF)

CE


RoHS

材料： 鍍銀黃銅

Material: Nickel-plated brass

工作温度： -40℃至100℃

Working temperature: -40℃ to 100℃



Thread	H mm	 mm	Beisit No.	Article No.
PG7	2,7	15	P07BR-LN	2.170.0701.03
PG9	3,0	18	P09BR-LN	2.170.0901.03
PG11	3,0	21	P11BR-LN	2.170.1101.03
PG13.5	3,0	23	P13BR-LN	2.170.1301.03
PG16	3,0	26	P16BR-LN	2.170.1601.03
PG21	3,5	32	P21BR-LN	2.170.2101.03
PG29	4,0	41	P29BR-LN	2.170.2901.03
PG36	5,0	51	P36BR-LN	2.170.3601.03
PG42	5,0	60	P42BR-LN	2.170.4201.03
PG48	5,5	64	P48BR-LN	2.170.4801.03
M12 x 1,5	2,6	15	M 12BR-LN	2.170.1201.01
M16 x 1,5	2,8	19	M 16BR-LN	2.170.1601.01
M20 x 1,5	3,0	23	M 20BR-LN	2.170.2001.01
M25 x 1,5	3,5	29	M 25BR-LN	2.170.2501.01
M32 x 1,5	4,0	36	M 32BR-LN	2.170.3201.01
M40 x 1,5	4,5	45	M 40BR-LN	2.170.4001.01
M50 x 1,5	5,5	55	M 50BR-LN	2.170.5001.01
M63 x 1,5	6,0	70	M 63BR-LN	2.170.6301.01
G(PF)1/4"	4	17	G14BR-LN	2.170.1401.05
G(PF)3/8"	4,5	19	G38BR-LN	2.170.3801.05
G(PF)1/2"	5	24	G12BR-LN	2.170.1201.05
G(PF)3/4"	5	30	G34BR-LN	2.170.3401.05
G(PF)1"	6	40	G100BR-LN	2.170.1001.05
G(PF)1 1/4"	6	50	G114BR-LN	2.170.5401.05
G(PF)1 1/2"	6	57	G112BR-LN	2.170.3201.05
G(PF)2"	6	64	G200BR-LN	2.170.2001.05

