

PG型/M型/G(PF)型圓形堵塞件
PG Type /M Type /G(PF) Type Nylon Screw Plugs




→ PG/M/G(PF)

CE IP68 RoHS

材料： 採用UL認可的尼龍材料
保護等級： IP68
工作溫度： -40℃至100℃
顏色種類： 灰色、黑色、
其他顏色可定做
材料種類： V0或F1可定做

Material: PA (NYLON), UL 94 V-2
Protection degree: IP68
Working temperature: -40℃ to 100℃
Color: Grey(RAL7035), Black(RAL9005),
other colors customized.
Material options: V0, or F1 can be offered upon request.

■ PROFILE



Thread øD1	GL mm	H mm	W mm	Beisit No. RAL7035 ●	Article No. RAL7035	Beisit No. RAL9005 ●	Article No. RAL9005
PG7	8,5	12,5	15	SPP0709	1.284.0701.4230-0	SPP0709B	1.284.0703.4230-0
PG9	8,5	13	19	SPP0909	1.284.0901.4230-0	SPP0909B	1.284.0903.4230-0
PG11	9	13	22	SPP1109	1.284.1101.4230-0	SPP1109B	1.284.1103.4230-0
PG13.5	9	13	25	SPP1309	1.284.1301.4230-0	SPP1309B	1.284.1303.4230-0
PG16	10,5	15	27	SPP1611	1.284.1601.4230-0	SPP1611B	1.284.1603.4230-0
PG21	10,5	15,5	33	SPP2111	1.284.2101.4230-0	SPP2111B	1.284.2103.4230-0
PG29	11,5	16	44	SPP2912	1.284.2901.4230-0	SPP2912B	1.284.2903.4230-0
PG36	13,5	18	55	SPP3614	1.284.3601.4230-0	SPP3614B	1.284.3603.4230-0
PG42	13,5	18,5	62	SPP4214	1.284.4201.4230-0	SPP4214B	1.284.4203.4230-0
PG48	14,5	19,5	68	SPP4815	1.284.4801.4230-0	SPP4815B	1.284.4803.4230-0
M12	8,5	12,5	15	SPM1209	1.284.1201.4030-0	SPM1209B	1.284.1203.4030-0
M16	8,5	13	19	SPM1609	1.284.1601.4030-0	SPM1609B	1.284.1603.4030-0
M20	7,5	13	25	SPM2009	1.284.2001.4030-0	SPM2009B	1.284.2003.4030-0
M20	7,5	11,5	25	SPM2008	1.284.2091.4030-0	SPM2008	1.284.2093.4030-0
M25	10,5	15,5	30	SPM2511	1.284.2501.4030-0	SPM2511B	1.284.2503.4030-0
M32	10,5	16	38	SPM3211	1.284.3201.4030-0	SPM3211B	1.284.3203.4030-0
M40	11,5	16	46	SPM4012	1.284.4001.4030-0	SPM4012B	1.284.4003.4030-0
M50	13,5	18	56	SPM5014	1.284.5001.4030-0	SPM5014B	1.284.5003.4030-0
M63	14	19	68	SPM6314	1.284.6301.4030-0	SPM6314B	1.284.6303.4030-0
G(PF) 1/4	6,5	10,5	17	SPG1407	1.284.1401.4530-0	SPG1405B	1.284.1403.4530-0
G(PF) 3/8	8	12,4	20,5	SPG3808	1.284.3801.4530-0	SPG3807B	1.284.3803.4530-0
G(PF) 1/2	8	12	26	SPG1208	1.284.1201.4530-0	SPG1206B	1.284.1203.4530-0
G(PF) 3/4	10	15	32	SPG3410	1.284.3401.4530-0	SPG3408B	1.284.3403.4530-0
G(PF) 1	12	17,5	40	SPG10012	1.284.1001.4530-0	SPG10010B	1.284.1003.4530-0
G(PF) 1 1/4	13	17,5	49	SPG11413	1.284.5401.4530-0	SPG11411B	1.284.5403.4530-0

