

LK3238 series fan-and-filter

148x148mm | 65-85 m³/h



Colour	RAL7035,color can be customized
Protection category	IP54 standard, IP55 plus precision filter mat, IP56 plus precision filter mat and protective cover.

Power indicator light



Customizable different colors






Filter mat replacement method



Dimensions

Exit filter LK 3238.300



Model No.fan-and-filter unit LK	3238.230-LK	3238.115-LK	3238.024-LK
Model No.fan-and-filter unit EMC	3238.230-EMC	3238.115-EMC	3238.024-EMC
Rated operating voltage,frequency V,Hz	230V, 50/60Hz	115V, 50/60Hz	24V (DC)
Air throughput,unimpeded air flow	65-85 m³/h		85 m³/h
Air throughput with Exit filter including standard filter mat	1 x LK 3238.300: 55-70 m³/h		
Axial fan	Self-starting shaded pole motor		DC motor
Rated current max.	0.12-0.10 A	0.24-0.20 A	0.35 A
Rated Power	19.0-14.0 W		7.7 W
Noise level	36-40 dB(A)		40 dB(A)
Operating temperature range	-30 - +70 °C		
Model No. Exit filter LK / EMC	3238.300 / 3238.300-EMC		
Design	Made of injection-moulded thermoplastic, customizable flame retardant materials, consistent with UL94-V0 self-extinguishing.		