

LK3240-M series fan-and-filter

254x254mm | 230-265 m³/h



Colour	RAL7035,color can be customized
Protection category	IP54 standard, IP55 plus precision filter mat, IP56 plus precision filter mat and protective cover.


Power indicator light






Customizable different colors



Filter mat replacement method



Dimensions



Exit filter LK 3240.300



Model No.fan-and-filter unit LK	3240-M.230-LK	3240-M.115-LK
Model No.fan-and-filter unit EMC	3240-M.230-EMC	3240-M.115-EMC
Rated operating voltage,frequency V,Hz	230V, 50/60Hz	115V, 50/60Hz
Air throughput,unimpeded air flow	230-265 m³/h	
Air throughput with Exit filter including standard filter mat	1 x LK 3240.300: 170-205 m³/h 2 x LK 3240.300: 200-230 m³/h	1 x LK 3240.300: 190-215 m³/h
Axial fan	Self-starting shaded pole motor	
Rated current max.	0.25-0.20 A	0.52-0.43 A
Rated Power	37.0-33.0 W	
Noise level	46-50 dB(A)	
Operating temperature range	-30 - +70 °C	
Model No. Exit filter LK / EMC	3240.300 / 3240.300-EMC	
Design	Made of injection-moulded thermoplastic, customizable flame retardant materials, consistent with UL94-V0 self-extinguishing.	