


article#	25712-sr
article description	Safety connector lid nat IP54 red series TopTaurus2
description long	Safety connector series TopTaurus2 with hinged lid color: black-red, material: PA6 2-component rubberized screwless quick lock system for housing cover and strain relief earthing system: Austrian/German 16A/ 250V AC / 3p (2P+E), protection rating: IP54
GTIN (EAN)	9003399454790
country of origin	AT
customs number	85366990
net weight	0.132 kg
packaging quantity	10
minimum order quantity	10

ETIM 9.0	EC001327
Model	Coupler CEE 7/3 (Typ F)
Material	Plastic
For heavy conditions according to VDE	True
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
Colour	Red
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A

K (cable Ø)	6-14 mm
SW	21 mm
wire flexible	1-2,5 mm ²
contact screws	80 Ncm
strain relief	400 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C
IK-code *)	IK09



*) The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. PC Electric GmbH has therefore tested the IK-codes of these products in accordance with IEC 62262 and according to the test method of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40°C and a relative humidity of 95%.



<https://www.pcelectric.at/shop/en/?func=detail&artnr=25712-sr>