


Solid-rubber distribution boxes – wall mounting Series TRAUNSEE

Series TRAUNSEE

- **Socket outlet combination acc. EN 61439**
- Solid rubber enclosure
- **Dimensions HxWxD = 260x165x90**
- Ready wired for connection
- **IP54** (IP67 on request)

Standard version:

- Protective insulation via 4-way wall fastening outside of wiring space
- All outer metal parts made out of stainless steel, captive screws
- Ready wired on main connecting terminal
- Cable gland IP68 on top
- CEE-sockets and safety sockets made of PA6, contacts nickel plated, sockets individual exchangeable



Layout examples: (other combinations on request!)

Layout	CEE 400V 5p			SS 250V	Protection		Connection	VS InA RDF	Cat.No.
	63A	32A	16A	16A	RCD	MCB			
				3	1xRCD 40A/4/0.03A (TYPE A 40AT)	3xMCB 16A 1p-C	1xM25 (ø13-18mm) top 1xM25 (blind cap) bottom	InA 32A RDF 0,8	9216140
		1		1	1xRCD 40A/4/0.03A (TYPE A 40AT)	1xMCB 16A 1p-C	1xM32 (ø18-25mm) top 1xM32 (blind cap) bottom	InA 32A RDF 0,6	9216427
				4			1xM20 (ø10-14mm) top 1xM20 (blind cap) bottom	max.16A	9216027
			1	2			1xM20 (ø10-14mm) top	max.16A	9216237
				4			2xterminal 3p 10mm² 2xM20 (ø10-14mm) top	max.16A	9216111
			1	2			1xterminal 5p 10mm² 1xterminal 3p 10mm² 1xM25 (ø13-18mm) top 1xM20 (ø10-14mm) top	max.16A	9216231
		1		2			1xterminal 5p 10mm² 1xterminal 3p 10mm² 1xM32 (ø18-25mm) top 1xM25 (ø13-18mm) top	max.16A max.32A	9216236